

# RiiO Sun II

- All-in-one Solar Inverter -



RiiO Sun II is a versatile transformer-based all-in-one solar inverter, designed for backup power, off-grid and ESS applications, integrating a pure sine wave inverter, battery charger, MPPT solar charge controller and a rapid 4ms automatic transfer switch in a compact casing. It's engineered to handle high surge loads and ensures continuous operation of critical load during outages. Outperforming conventional transformer-based inverters, Riio Sun II transformer-based hybrid inverter maximizes solar energy use by preferentially powering loads, charging batteries, and feeding surplus back to the grid, minimizing waste.

Additionally, Riio Sun II enhances energy self-consumption, supports grid feed-in for utility credits, and optimizes costs with peak shaving and time-of-use strategies.

## Enhanced Flexibility

- Versatile for backup power, off-grid and ESS
- Parallel & three-phase up to 9 units, 72kVA
- Built-in a smart port for Gen input or 2nd AC output\*1
- DC Coupling and AC Coupling
- 2 MPPT trackers for flexible system design and higher yields\*2
- Up to 250V PV open circuit voltage
- Higher PV charging power and current
- AGS function, Power Control & Power Assist
- Compatible with mainstream lithium battery brands and generators
- Optional to work without battery\*3

## Easy O&M

- All-in-one design for easy installation
- Auto restart when the PV or AC is recovering
- Local monitoring via E4 LCD Monitor
- Remote monitoring and control via Nova Web & APP

## Superior Reliability

- Transformer-based, high surge power
- 4ms ultra-fast switch to battery power
- Maximize solar energy utilization and minimize energy waste
- ECO Mode to prolong backup time
- Extremely low self-consumption power
- Max inverter efficiency 95%, max MPPT efficiency 98%

## ESS Capabilities

- Maximize self-consumption
- Lower electricity bills via peak shaving & time-of-use
- AC Coupling retrofitting
- Grid feed-in for utility credits

\*1-2: Only available for 5kVA/6kVA/8kVA model

\*3: Only for single-unit application with stable AC bypass supply, PV energy as a supplement for AC bypass

Model	RiiO Sun II 1KVA-L Kit	RiiO Sun II 1.5KVA-M Kit	RiiO Sun II 2KVA-M Kit	RiiO Sun II 3KVA-M Kit
Power Assist	Yes			
AC Input Range	175~265 VAC / 45~65Hz			
AC Input Current (Transfer Switch) (A)	16	16	32	32
<b>Inverter</b>				
Nominal Battery Voltage / Input Voltage (V)	12 / 10.5-17	24 / 21-34		
AC Output Voltage (VAC)	220/230/240 ± 2%			
AC Output Frequency (Hz)	50/60 ± 0.1%			
Harmonic Distortion	<2%			
Cont. Output Power at 25°C (VA)	1000	1500	2000	3000
Max Output Power at 25°C (W)	1000	1500	2000	3000
Peak Power (W)	2000	3000	4000	6000
Surge	300%			
Maximum Efficiency	89%	91%	91%	91%
Zero Load Power (W)	12	12	13	17
<b>Charger</b>				
Charge Voltage 'Absorption' / 'Float' (V)	14.4 / 13.8	28.8 / 27.6		
Battery Types	AGM / GEL / OPzV / Lead-Carbon / Flooded / Traction / Lithium			
Max AC Charge Current (A)	40	35	40	70
Temperature Compensation	Yes			
<b>Solar Charge Controller</b>				
Max Output Current (A)	60	60	80	80
Maximum PV Open Circuit Voltage (V)	150	150	150	150
MPPT Voltage Range (V)	30~145	40~145		
Number Of MPPT Trackers	1	1	1	1
Maximum PV Input Current Per Tracker (A)	36	36	36	36
Max PV Short Circuit Current Per Tracker	40	40	40	40
Maximum Charge Power	860W @ 14.4V	1720W @ 28.8V	2300W @ 28.8V	2300W @ 28.8V
Allowable Maximum PV Power Per Tracker	1200	2300	3600	3600
Charge Voltage 'Absorption' (V) / 'Float' (V)	14.4 / 13.8	28.8 / 27.6		
MPPT Charger Maximum Efficiency	98%			
MPPT Efficiency	>99.5%			
Protection	a) output short circuit; b) overload; c) battery voltage too high; d) battery voltage too low; e) temperature too high; f) input voltage out of range;			
<b>General Data</b>				
AC Out1 Current (A)	16	16	32	32
Smart Port Current (A)	N/A			
Transfer Time	4ms (<15ms in Weak AC source Mode)			
Protection	a) output short circuit; b) overload; c) battery voltage too high; d) battery voltage too low; e) temperature too high; f) input voltage out of range; g) input voltage ripple too high; h) Fan block			
General Purpose Com. Port	RS485 (GPRS, WLAN optional)			
Programmable Relay	1x (30Vdc/3A or 250Vac/3A)			
Operating Temperature Range	-20°C to 65°C			
Relative Humidity In Operation	95% without condensation			
Altitude (m)	2000			
<b>Mechanical Data</b>				
Dimension (mm) (max)	462*255*144		499*272*144	
Net Weight (kg)	12	13	14	18
Cooling	Forced fan			
Protection Index	IP21			
<b>Standards</b>				
Safety	EN-IEC 62477-1, EN-IEC 62109-1, EN-IEC 62109-2			
EMC	EN-IEC 61000-6-1, EN-IEC 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12			
Grid Regulation	EN 50549-1, EN 50549-10		RD 1699, NRS 097, EN 50549-1, EN 50549-10	

Note: The Kinergy II-WiFi wireless data logger is included with the RiiO Sun II Kit version.

Model	RiiO Sun II 2KVA- S Kit	RiiO Sun II 3KVA- S Kit	RiiO Sun II 4KVA- S Kit	RiiO Sun II 5KVA- S Kit	RiiO Sun II 6KVA- S Kit	RiiO Sun II 8KVA- S Kit	RiiO Sun II 8KVA- S Pro Kit
Power Assist	Yes						
AC Input Range	175~265 VAC / 45~65Hz						
AC Input Current (Transfer Switch) (A)	20	32	32	50	50	50	50
<b>Inverter</b>							
Nominal Battery Voltage / Input Voltage (V)	48 / 42~68						
AC Output Voltage (VAC)	220/230/240 ± 2%						
AC Output Frequency (Hz)	50/60 ± 0.1%						
Harmonic Distortion	<2%						
Cont. Output Power at 25°C (VA)	2000	3000	4000	5000	6000	8000	8000
Max Output Power at 25°C (W)	2000	3000	4000	5000	6000	8000	8000
Peak Power (W)	4000	6000	8000	10000	12000	16000	16000
Surge	300%						
Maximum Efficiency	93%	93%	93%	94%	94%	95%	95%
Zero Load Power (W)	14	17	19	22	25	32	32
<b>Charger</b>							
Charge Voltage 'Absorption' / 'Float' (V)	57.6 / 55.2						
Battery Types	AGM / GEL / OPzV / Lead-Carbon / Flooded / Traction / Lithium						
Max AC Charge Current (A)	20	35	50	60	70	90	90
Temperature Compensation	Yes						
<b>Solar Charge Controller</b>							
Max Output Current (A)	40	60	60	100 (50 per tracker)			120 (60 per tracker)
Maximum PV Open Circuit Voltage (V)	250	250	250	250	250	250	250
MPPT Voltage Range (V)	65~245						
Number of MPPT Trackers	1	1	1	2	2	2	2
Maximum PV Input Current Per Tracker (A)	36	36	36	36+36	36+36	36+36	36+36
Max PV Short Circuit Current Per Tracker	40	40	40	40+40	40+40	40+40	40+40
Maximum Charge Power	2300W @ 57.6V	3450W @ 57.6V	3450W @ 57.6V	5760W @ 57.6V total, 2880W @ 57.6V per tracker			6900W @ 57.6V total 3450W @ 57.6V per tracker
Allowable Maximum PV Power Per Tracker	3600	5200	5200	4400 + 4400			5200 + 5200
Charge Voltage 'Absorption' (V) / 'Float' (V)	57.6 / 55.2						
MPPT Charger Maximum Efficiency	98%						
MPPT Efficiency	>99.5%						
Protection	a) output short circuit; b) overload; c) battery voltage too high; d) battery voltage too low; e) temperature too high; f) input voltage out of range;						
<b>General Data</b>							
AC Out1 Current (A)	20	32	32	50	50	50	50
Smart Port Current (A)	N/A			50	50	50	50
Transfer Time	4ms (<15ms in Weak AC source Mode)						
Protection	a) output short circuit; b) overload; c) battery voltage too high; d) battery voltage too low; e) temperature too high; f) input voltage out of range; g) input voltage ripple too high; h) Fan block						
General Purpose Com. Port	RS485 (GPRS, WLAN optional)						
Programmable Relay	1x (30Vdc/3A or 250Vac/3A)						
Operating Temperature Range	-20°C to 65°C						
Relative Humidity in Operation	95% without condensation						
Altitude (m)	2000						
<b>Mechanical Data</b>							
Dimension (mm) (max)	462*255*144	499*272*144		570*310*154		620*320*164	
Net Weight (kg)	14	18	20	29	31	34	
Cooling	Forced fan						
Protection Index	IP21						
<b>Standards</b>							
Safety	EN-IEC 62477-1, EN-IEC 62109-1, EN-IEC 62109-2						
EMC	EN-IEC 61000-6-1, EN-IEC 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12						
Grid Regulation	RD 1699, NRS 097, EN 50549-1, EN 50549-10						

Note: The Kinergy II-WiFi wireless data logger is included with the RiiO Sun II Kit version.

# RiiO Sun II

All-in-one Solar Inverter

